

ANSMANN APS 2250H

Universal power supply 12 - 24 V DC to power many small electrical devices

Features

- 12 - 24 V DC universal power supply to power many small electrical devices
- Regulated output voltage
- Short circuit proof
- World wide application possible due to wide range input (100-240V AC)
- Selectable output voltages by a rotary switch: 3V / 4,5V / 5V / 6V / 7,5V / 9V / 12V DC;
- Maximum output current: 2250mA at 12V, 1800mA at 15V, 1500mA at 18V, 1400mA at 19V, 1350mA at 20V, 1200mA at 22V, 1000mA at 24V;
- Maximum output power: 27 W



Voltage



Charging current



Power



Cable length



Polarity inverter



Adjustable Voltage



Article number: 1201-0026

Product content: APS 2250H, EU power plug with 2m cable, 7 changeable adapters with 1.8m cable

4 013674 164141

Specifications

Input voltage	100 - 240V AC		
Max. output current	2,25 A		
suitable for	Universal		
Maximum power	27 W		
Charging currents	**Voltage**	**Max. current**	**Max. power**
	12,0 V	2,3 A	27,0 W
	15,0 V	1,8 A	27,0 W
	18,0 V	1,5 A	27,0 W
	19,0 V	1,4 A	26,6 W
	20,0 V	1,4 A	27,0 W
	22,0 V	1,2 A	26,4 W
	24,0 V	1,0 A	24,0 W
Secondary plug set	Yes		
Polarity socket	Yes		
Stabilized	Yes		
Voltage range	12 - 24 V DC		
Average operational efficiency	86,9 %		
Efficiency at low load	83,0 %		
Power consumption at no load	0,070 W		
Cable length	360 cm		
Color	black		
Packaging	cardboard box		
Operating temperature	0 - 25 °C		
Storage temperature	-25 - 70 °C		
Dimensions	53 × 32 × 100 mm		